

RECEIVED
CENTRAL FAX CENTER
JUN 19 2007

Application No: 10/733,343
Attorney's Docket No: ALC 3108

CLAIM AMENDMENTS

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims

1. (Previously Presented) A system for detecting a pattern in a data stream comprising:
 - a FIFO for receiving an N-bit wide data stream and a corresponding first clock signal at a first rate, and outputting the data stream as a W times N-bit wide data stream and a corresponding second clock signal at a second rate, where W is an integer natural number and the second rate equals the first rate divided by W;
 - a bus splitter for splitting the W times N-bit wide data stream into W data streams of width N;
 - a plurality (W) of RAMs, each RAM for storing data obtained by processing the pattern and for receiving a respective one of the data streams of width N as an address and the second clock signal as a clock, and each RAM being operable to output a portion of the data on an M-bit wide output bus in accordance with a value of the address;
 - a processor for receiving the portions of data on each M-bit wide output bus as data and the second clock signal as a clock, and being operable to determine whether the pattern is in the data stream in dependence upon the received portions of data and the received clock, and for outputting a pattern match signal indicating detection of the pattern in the data stream; and
 - a channel state RAM for storing the state of the processor and running C times slower the data rate.

Application No: 10/733,343
Attorney's Docket No: ALC 3108

2. (Original) The system as defined in claim 1 wherein the processor comprises shift/and combinatory logic and a register.
3. (Original) The system as defined in claim 1 having channelization functionality including an input channel register and a channel state RAM running C times slower than the first rate.
4. (Original) The system as defined in claim 3 wherein the processor includes means to update the channel state RAM in response to a state change.
5. (Previously Presented) A system for detecting a pattern in a data stream comprising:
 - an input stream register for receiving the data stream and a corresponding first clock signal at a first rate, and outputting the data stream and a corresponding second clock signal at a second rate;
 - a pattern RAM for storing a pattern to be detected;
 - a processor for receiving the data and the second clock signal as a clock, and being operable to determine whether the pattern is in the data stream in dependence upon the received data and the received clock, and for outputting a pattern match signal indicating detection of the pattern in the data stream
 - a channel state RAM for storing the state of the processor and running C times slower the data rate

Application No: 10/733,343
Attorney's Docket No: ALC 3108

a multiplexer that redirects either the contents of the processor's register or the contents of the channel state RAM to the processor; and

a channel register to switch the processor in dependence on the received data.

6. (Original) The system as defined in claim 5 wherein said input stream register is a FIFO for receiving an N-bit wide signal and having bus splitting means to divide said stream into W signals, each of said W signal provided to separate pattern RAMs.

7. (Original) The system as described in claim 1 wherein the data stream is of a known length.

8. (Original) The system as described in claim 5 wherein the data stream is of a known length.

9. (Original) The system as described in claim 1 adapted to detect a pattern of arbitrary length wherein the length is less than a set value.

10. (Original) The system as described in claim 5 adapted to detect a pattern of arbitrary length wherein the length is less than a set value.

Application No: 10/733,343
Attorney's Docket No: ALC 3108

11. (Original) The system as described in claim 9 wherein multiple engines are chained to detect a pattern of any arbitrary length.

12. (Currently Amended) ~~A processor for use in a pattern matching engine~~The system as described in claim 5,

the processor having combinatory logic means for receiving outputs from pattern matching RAMs;

a register and an And Gate for combining the outputs from respective ~~logic~~ logic means to output an indication of a matched pattern.

13. (Currently Amended) A method of detecting a pattern in a data stream comprising:

receiving, at a FIFO, an N-bit wide data stream and a corresponding first clock signal at a first rate, and outputting the data stream as a W times N-bit wide data stream and a corresponding second clock signal at a second rate, where W is an integer natural number and the second rate equals the first rate divided by W;

splitting the W times N-bit wide data stream into W data streams of width N;

providing a plurality (W) of RAMs, each RAM for storing data obtained by processing the pattern and for receiving a respective one of the data streams of width N as an address and the second clock signal as a clock, and each RAM being operable to output a portion of the data on an M-bit wide output bus in accordance with a value of the address;

Application No: 10/733,343
Attorney's Docket No: ALC 3108

receiving the portions of data on each M-bit wide output bus as data and the second clock signal as a clock at a processor, the processor being operable to determine whether the pattern is in the data stream in dependence upon the received portions of data and the received clock, and outputting a pattern match signal indicating detection of the pattern in the data stream; and

a channel state RAM for storing the state of the processor and running C times slower the ~~data-rate~~data rate.

14. (Original) The method as defined in claim 13 further comprising:

providing means for adding channelization functionality in order to separate the input stream into channels for pattern matching.

15. (Original) A method of detecting a pattern in a data stream comprising:

receiving the data stream and a corresponding first clock signal at a first rate at an input stream register and outputting the data stream and a corresponding second clock signal at a second rate;

storing a pattern to be detected at a pattern RAM;

receiving the data and the second clock signal as a clock at a processor, the processor being operable to determine whether the pattern is in the data stream in dependence upon the received data and the received clock, and outputting a pattern match signal indicating detection of the pattern in the data stream;

Application No: 10/733,343
Attorney's Docket No: ALC 3108

providing a channel state RAM for storing the state of the processor and running C times
slower the data rate
redirecting either the contents of the processor's register or the contents of the channel
state RAM to the processor; and
switching the processor in dependence on the received data.

16. (Original) The method as defined in claim 15 wherein multiple pattern matching
RAMs are provided to provide scalability.